

Ex db behuizingen voor speciale toepassingen Ex db enclosures for special applications

Technische informatie

Ex markering: Ⓜ II 2G Ex db [...] IIC T3..T6 Gb
 Geschikt voor zone 1 en 2
 Omgevingstemperatuur: $-20^{\circ}\text{C} \leq \text{Ta} \leq 40^{\circ}\text{C}$
 Omgevingstemperatuur optioneel: $-20^{\circ}\text{C} \leq \text{Ta} \leq 55^{\circ}\text{C}$
 Beschermingsgraad: IP65 / IP66
 Materiaal: koperarm aluminium LM6 (koper <0,05%)
 Optioneel: offshore coating in RAL kleur

Conform de standaards: IEC60079 en EN60079

Compleet met anti condens heater

Technical data:

Ex mark: Ⓜ II 2G Ex db [...] IIC T3..T6 Gb
 Can be used in zone 1 and 2
 Ambient temperature: $-20^{\circ}\text{C} \leq \text{Ta} \leq 40^{\circ}\text{C}$
 Optional ambient temperature: $-20^{\circ}\text{C} \leq \text{Ta} \leq 55^{\circ}\text{C}$
 Degree of protection: IP65 / IP66
 Material: copper free aluminium LM6 (copper <0.05%)
 Optional: offshore coating in RAL colour

Meets the standards: IEC60079 and EN60079

Complete with anti condens heater



Camerabehuizing Ex d - type INDEX.GUB.CAM
Camera box Ex d - type INDEX.GUB.CAM

