



Omschrijving:

Deze bekende, kleine kastjes worden veelal gebruikt als aansluit- of verbindingskast. Daarnaast vindt deze kast toepassing als behuizing voor o.a. transmitters, gasdetectors of temperatuursensoren. Er zijn verschillende uitvoeringen met gaten aan de zijkant en aan de onderzijde leverbaar, zie de tabel op blz. A12. De kasten zijn voorzien van tapgaten, sommige uitvoeringen zijn leverbaar met een montagebeugel.

Description:

These well known, small boxes are often used as connection or pulling box. Furthermore transmitters, gas detectors or temperature sensors are mounted inside this enclosure. Different types, with entries on the side and on the bottom are available, see table on page A12. The boxes have threaded holes, some types can be supplied including a mounting bracket.

Technische informatie

Ex markering: II 2G Ex db IIC T6 Gb
 II 2D Ex tD A21 T85°C Db
 Geschikt voor zone 1, 2, 21 en 22
 Omgevingstemperatuur: $-20^{\circ}\text{C} \leq T_a \leq 40^{\circ}\text{C}$
 Beschermingsgraad: IP66 / IP67
 Materiaal: koperarm aluminium LM6 (koper <0,05%)
 Optioneel: offshore coating in RAL kleur
 Optioneel: RVS 316

Conform de standaards: EN60079

Technical data:

Ex mark: II 2G Ex db IIC T6 Gb
 II 2D Ex tb IIIC T85°C Db
 Can be used in zone 1, 2, 21 en 22
 Ambient temperature: $-20^{\circ}\text{C} \leq T_a \leq 40^{\circ}\text{C}$
 Degree of protection: IP66 / IP67
 Material: copper free aluminium LM6 (copper <0.05%)
 Optional: offshore coating in RAL colour
 Optional: Stainless Steel 316

Meets the standards: EN60079

Zone 1 & zone 2
Zone 21 & zone 22

Kabelingang Cable entry		D	A	H	S	Type
	1 Ingang in zijwand 1 Entry in side	1/2"	100	67	3	KOP - SFA 16
		3/4"	100	67	3	KOP - SFA 26
		1"	106	75	3	KOP - SFA 36
	2 Ingangen in zijwand 2 Entries in side	1/2"	100	67	3	KOP - SFC 16
		3/4"	100	67	3	KOP - SFC 26
		1"	106	75	3	KOP - SFC 36
	3 Ingangen in zijwand 3 Entries in side	1/2"	100	67	3	KOP - SFL 16
		3/4"	100	67	3	KOP - SFL 26
		1"	106	75	3	KOP - SFL 36
	4 Ingangen in zijwand 4 Entries in side	1/2"	100	67	3	KOP - SFT 16
		3/4"	100	67	3	KOP - SFT 26
		1"	106	75	3	KOP - SFT 36
	2 Ingangen in zijwand 2 Entries in side	1/2"	100	67	3	KOP - SFX 16
		3/4"	100	67	3	KOP - SFX 26
		1"	106	75	3	KOP - SFX 36
	1 Ingang zijwand + 1 ingang bodem 1 Entry in side + 1 entry in bottom	1/2"	100	67	3	KOP - GUAB 16
		3/4"	100	67	3	KOP - GUAB 26
		1"	106	75	3	KOP - GUAB 36
	2 Ingangen zijwand + 1 ingang bodem 2 Entries in side + 1 entry in bottom	1/2"	100	67	3	KOP - GUAP 16
		3/4"	100	67	3	KOP - GUAP 26
		1"	106	75	3	KOP - GUAP 36
	3 Ingangen zijwand + 1 ingang bodem 3 Entries in side + 1 entry in bottom	1/2"	100	67	3	KOP - GUAW 16
		3/4"	100	67	3	KOP - GUAW 26
		1"	106	75	3	KOP - GUAW 36
	2 Ingangen zijwand + 1 ingang bodem 2 Entries in side + 1 entry in bottom	1/2"	100	67	3	KOP - GUAM 16
		3/4"	100	67	3	KOP - GUAM 26
		1"	106	75	3	KOP - GUAM 36

Alle SF types worden geleverd met montagebeugel
All SF types complete with mounting bracket

Afmetingen
Dimensions

