

### Technische informatie:

Ex markering:  $\text{Ex II 2G Ex db eb IIC Gb } (-20^{\circ}\text{C} \leq T_a \leq 60^{\circ}\text{C})$   
 $\text{Ex db eb IIB Gb } (-40^{\circ}\text{C} \leq T_a \leq 60^{\circ}\text{C})$

Geschikt voor zone 1 en 2

Spanning 230/400V - 50/60 Hz.

Kortsluitstroom: 6 kA

Karakteristiek: C

Optioneel is karakteristiek D mogelijk

Hulpcontacten: 1xNO/1xNC - 250V/1A

Aansluitingen: 10 mm<sup>2</sup> / hulpcontacten 2,5 mm<sup>2</sup>

Conform de standaards: EN60079

### Technical data:

Ex mark:  $\text{Ex II 2G Ex db eb IIC Gb } (-20^{\circ}\text{C} \leq T_a \leq 60^{\circ}\text{C})$   
 $\text{Ex db eb IIB Gb } (-40^{\circ}\text{C} \leq T_a \leq 60^{\circ}\text{C})$

Can be used in zone 1 and 2

Voltage: 230/400V - 50/60 Hz.

Breaking capacity: 6 kA

Tripping curve: C

Optional tripping curve: D

Aux. contacts: 1xNO/1xNC - 250V/1A

Connections: 10 mm<sup>2</sup> / aux. contacts 2.5 mm<sup>2</sup>

Meets the standards: EN60079

Aantal polen Number of poles	Karakteristiek Tripping curve type	Nominale stroom (A) Rated current (A)	Gewicht (kg) Weight (kg)	Afmeting Size
1P	C, D	1, 2, 4, 6, 10, 16, 20, 25, 32, 40	0.85	1
2P	C, D	1, 2, 4, 6, 10, 16, 20, 25, 32, 40	1.07	2
3P	C, D	6, 10, 16, 20, 25, 32, 40	1.43	3
4P	C	6, 10, 16, 20, 25, 32, 40	1.90	4
1P+N	C	1, 2, 4	1.07	2
1P+N	C	6, 10, 16, 20, 25, 32, 40	0,85	1
3P+N	C, D	6, 10, 16, 20, 25, 32, 40	1.90	4

	Nominale stroom (A) Rated current (A)	Type	
	0.5	Z0511 BL - 0.5 - □ - □ - □ - □	
	1	Z0511 BL - 1 - □ - □ - □ - □	
	2	Z0511 BL - 2 - □ - □ - □ - □	
	3	Z0511 BL - 3 - □ - □ - □ - □	
	4	Z0511 BL - 4 - □ - □ - □ - □	
	6	Z0511 BL - 6 - □ - □ - □ - □	
	10	Z0511 BL - 10 - □ - □ - □ - □	
	16	Z0511 BL - 16 - □ - □ - □ - □	
	20	Z0511 BL - 20 - □ - □ - □ - □	
	25	Z0511 BL - 25 - □ - □ - □ - □	
	32	Z0511 BL - 32 - □ - □ - □ - □	
	40	Z0511 BL - 40 - □ - □ - □ - □	
	<p>Aantal polen    <b>1</b>-(1P)    <b>1N</b>-(1P+N)    <b>2</b>-(2P)    <b>3</b>-(3P)    <b>3N</b>-(3P+N)    <b>4</b>-(4P)</p> <p>Number of poles</p>		
	<p>Karakteristiek    <b>C</b></p> <p>Curve type        <b>D</b></p>		
<p>A = inclusief hulpcontacten 1NO + 1NC</p> <p>A = including auxiliary contacts 1NO + 1NC</p>			

Afmetingen Dimensions	Contactbezetting Contacts	Afmeting Size	Achter venster Behind window
	<p>1P 1P+N</p>	<p>Afmeting 1 Dimension 1</p>	<p>6 stuks 6 pcs 2 stuks 2 pcs</p>
	<p>2P 2P + hulpcontacten 2P + aux. contacts</p>	<p>Afmeting 2 Dimension 2</p>	<p>5 stuks 5 pcs 2 stuks 2 pcs</p>
	<p>3P 3P + hulpcontacten 3P + aux. contacts</p>	<p>Afmeting 3 Dimension 3</p>	<p>3 stuks 3 pcs 1 stuks 1 pcs</p>
	<p>3P+N 4P 3P + hulpcontacten 3P + aux. contacts 4P + hulpcontacten 4P + aux. contacts</p>	<p>Afmeting 4 Dimension 4</p>	<p>2 stuks 2 pcs 1 stuks 1 pcs</p>