

Technische informatie:

Ex markering: $\text{Ex II 2G Ex de IIC Gb } (-20^{\circ}\text{C} \leq \text{Ta} \leq 60^{\circ}\text{C})$
 $\text{Ex de IIB Gb } (-40^{\circ}\text{C} \leq \text{Ta} \leq 60^{\circ}\text{C})$

Geschikt voor zone 1 en 2

Schakelvermogen: 5A

Spoelspanning: 12, 24 en 110 VDC / 24, 115 en 230 VAC

Aansluitingen: 2,5 mm²

Gewicht: 0,8 kg

Conform de standaards: EN60079

Technical data:

Ex mark: $\text{Ex II 2G Ex de IIC Gb } (-20^{\circ}\text{C} \leq \text{Ta} \leq 60^{\circ}\text{C})$
 $\text{Ex de IIB Gb } (-40^{\circ}\text{C} \leq \text{Ta} \leq 60^{\circ}\text{C})$

Can be used in zone 1 and 2

Switching capacity: 5A

Coil voltages: 21, 24 and 110 VDC / 24, 115 and 230 VAC

Connections: 2.5 mm²

Weight: 0.8 kg

Meets the standards: EN60079

Afbeelding Illustration	Aansluitschema Wiring diagram	Spoelspanning Coil voltage	Type
		12 VDC 24 VDC 110 VDC 24 VAC 115 VAC 230 VAC	Z0512BMY / 10 Z0512BMY / 11 Z0512BMY / 14 Z0512BMY / 01 Z0512BMY / 04 Z0512BMY / 05

Afmetingen Dimensions

