

Polyamide kabelwartel Ex e Polyamide cable gland Ex e

Technische informatie:

Ex marking: $\text{Ex II 2GD Ex e II Ex tD A21}$
 Geschikt voor zone 1, 2, 20, 21 and 22
 Omgevingstemperatuur: $-40^{\circ}\text{C} \leq \text{Ta} \leq 70^{\circ}\text{C}$
 Beschermingsgraad: IP66
 Materiaal: Polyamide


Conform de standaards: EN60079 en EN61241

Technical data:

Ex mark: $\text{Ex II 2GD Ex e II Ex tD A21}$
 Can be used in zone 1, 2, 20, 21 and 22
 Ambient temperature: $-40^{\circ}\text{C} \leq \text{Ta} \leq 70^{\circ}\text{C}$
 Degree of protection: IP66
 Material: Polyamide

Meets the standards: EN60079 and EN61241

Polyamide kabelwartel Ex e Polyamide cable gland Ex e


Afbeelding Illustration	D	C		K (mm)	L (mm)	LH (mm)	Type
		Min.	Max.				
 Ex e	M12x1.5	4	7	15	8	22	IE2012
	M16x1.5	5.5	10	20	8	27	IE2016
	M20x1.5	5.5	13	24	8	31	IE2020
	M25x1.5	8	17	29	8	36	IE2025
	M32x1.5	12	21	36	10	43	IE2032
	M40x1.5	17	28	46	10	47	IE2040
	M50x1.5	22	35	55	12	54	IE2050
	M63x1.5	27	48	68	12	57	IE2063
	M25x1.5	4x3	4x6	29	11	36	IE2024
	M32x1.5	4x5	4x7	36	12	43	IE2034

Polyamide kabelwartel Ex i Polyamide cable gland Ex i


D	C		K (mm)	L (mm)	LH (mm)	Type
	Min.	Max.				
M12x1.5	4	7	15	8	22	IE2012 BU
M16x1.5	5.5	10	20	8	27	IE2016 BU
M20x1.5	5.5	13	24	8	31	IE2020 BU
M25x1.5	8	17	29	8	36	IE2025 BU
M32x1.5	12	21	36	10	43	IE2032 BU
M40x1.5	17	28	46	10	47	IE2040 BU
M50x1.5	22	35	55	12	54	IE2050 BU
M63x1.5	27	48	68	12	57	IE2063 BU
M25x1.5	4x3	4x6	29	11	36	IE2024 BU
M32x1.5	4x5	4x7	36	12	43	IE2034 BU

Ex i

Afmetingen Dimensions



Enkelvoudig
Single-hole type



Meervoudig
Multi-hole type

