

**Blindplug Ex d / Ex e
Plug Ex d / Ex e**

Technische informatie:

Ex markering: Ex I/II 2 G Ex d I/IC T6 Gb
 Ex I/II 2 G Ex e I/IC T6 Gb
 Ex I/II 2 D Ex tb IIIC T80° Db IP66
 Geschikt voor zone 1, 2, 20, 21 and 22
 Omgevingstemperatuur: $-70^{\circ}\text{C} \leq \text{Ta} \leq 220^{\circ}\text{C}$
 Beschermingsgraad: IP66
 Materiaal: messing
 Optioneel materiaal: messing vernikkeld / RVS 316

Conform de standaards: EN60079

Technical data:

Ex mark: Ex I/II 2G Ex d I/IC T6 Gb
 Ex I/II 2G Ex e I/IC T6 Gb
 Ex I/II 2D Ex tb IIIC T80° Db IP66
 Can be used in zone 1, 2, 20, 21 and 22
 Ambient temperature: $-70^{\circ}\text{C} \leq \text{Ta} \leq 220^{\circ}\text{C}$
 Degree of protection: IP66
 Material: brass
 Optional material: brass nickel plated / Stainless Steel 316

Meets the standards: EN60079

Afbeelding Illustration	Grootte Size	Type
	M 16	IPLUG.M16 <input type="checkbox"/>
	M 20	IPLUG.M20 <input type="checkbox"/>
	M 25	IPLUG.M25 <input type="checkbox"/>
	M 32	IPLUG.M32 <input type="checkbox"/>
	M 40	IPLUG.M40 <input type="checkbox"/>
	M 50	IPLUG.M50 <input type="checkbox"/>
	M 63	IPLUG.M63 <input type="checkbox"/>
	M 75	IPLUG.M75 <input type="checkbox"/>
	M 90	IPLUG.M90 <input type="checkbox"/>
	3/8" NPT	IPLUG.N3/8 <input type="checkbox"/>
	1/2" NPT	IPLUG.N1/2 <input type="checkbox"/>
	3/4" NPT	IPLUG.N3/4 <input type="checkbox"/>
	1" NPT	IPLUG.N1 <input type="checkbox"/>
	1 1/4" NPT	IPLUG.N1 1/4 <input type="checkbox"/>
	1 1/2" NPT	IPLUG.N1 1/2 <input type="checkbox"/>
	2" NPT	IPLUG.N2 <input type="checkbox"/>
	2 1/2" NPT	IPLUG.N2 1/2 <input type="checkbox"/>
	3" NPT	IPLUG.N3 <input type="checkbox"/>
	PG 13,5	IPLUG.P13 <input type="checkbox"/>
	PG 16	IPLUG.P16 <input type="checkbox"/>
PG 21	IPLUG.P21 <input type="checkbox"/>	
PG 29	IPLUG.P29 <input type="checkbox"/>	
PG 36	IPLUG.P36 <input type="checkbox"/>	

Messing - Brass - B
 Vernikkeld - Nickel plated - N
 RVS 316 - Stainless Steel 316 - S

Overige uitvoeringen en maten op aanvraag
 Other types and dimensions on request