

Blindplug Ex d / Ex e
Plug Ex d / Ex e

Technische informatie:

Ex marking: Ex I/II 2 G Ex db I/II C T6 Gb
 Ex I/II 2 G Ex eb I/II C T6 Gb
 Ex I/II 2 D Ex tb I/II C T80° Db IP66

Geschikt voor zone 1, 2, 20, 21 and 22

Omgevingstemperatuur: $-70^{\circ}\text{C} \leq \text{Ta} \leq 220^{\circ}\text{C}$

Beschermingsgraad: IP66

Materiaal: messing / messing vernikkeld / RVS 316

Conform de standaards: IEC60079 en EN60079

Technical data:

Ex mark: Ex I/II 2G Ex db I/II C T6 Gb

Ex I/II 2G Ex eb I/II C T6 Gb

Ex I/II 2D Ex tb I/II C T80° Db IP66

Can be used in zone 1, 2, 20, 21 and 22

Ambient temperature: $-70^{\circ}\text{C} \leq \text{Ta} \leq 220^{\circ}\text{C}$

Degree of protection: IP66

Material: brass / brass nickel plated / Stainless Steel 316

Meets the standards: IEC60079 and EN60079

Afbeelding Illustration	Grootte Size	Type	
	M 16	IPLUG.M16 <input type="checkbox"/>	
	M 20	IPLUG.M20 <input type="checkbox"/>	
	M 25	IPLUG.M25 <input type="checkbox"/>	
	M 32	IPLUG.M32 <input type="checkbox"/>	
	M 40	IPLUG.M40 <input type="checkbox"/>	
	M 50	IPLUG.M50 <input type="checkbox"/>	
	M 63	IPLUG.M63 <input type="checkbox"/>	
	M 75	IPLUG.M75 <input type="checkbox"/>	
	M 90	IPLUG.M90 <input type="checkbox"/>	
	3/8" NPT	IPLUG.N3/8 <input type="checkbox"/>	
	1/2" NPT	IPLUG.N1/2 <input type="checkbox"/>	
	3/4" NPT	IPLUG.N3/4 <input type="checkbox"/>	
	1" NPT	IPLUG.N1 <input type="checkbox"/>	
	1 1/4" NPT	IPLUG.N1 1/4 <input type="checkbox"/>	
	1 1/2" NPT	IPLUG.N1 1/2 <input type="checkbox"/>	
	2" NPT	IPLUG.N2 <input type="checkbox"/>	
	2 1/2" NPT	IPLUG.N2 1/2 <input type="checkbox"/>	
	3" NPT	IPLUG.N3 <input type="checkbox"/>	
PG 13,5	IPLUG.P13 <input type="checkbox"/>		
PG 16	IPLUG.P16 <input type="checkbox"/>		
PG 21	IPLUG.P21 <input type="checkbox"/>		
PG 29	IPLUG.P29 <input type="checkbox"/>		
PG 36	IPLUG.P36 <input type="checkbox"/>		

Messing - Brass - B
 Vernikkeld - Nickel plated - N
 RVS 316 - Stainless Steel 316 - S