

Aardlip Ex d / Ex e
Earthing tag Ex d / Ex e

Technische informatie:

Ex markering: Ⓢ I/II 2 G Ex db I/IC T6 Gb
Ⓢ I/II 2 G Ex eb I/IC T6 Gb
Ⓢ III 2 D Ex tb IIIC T80° Db IP66

Geschikt voor zone 1, 2, 20, 21 and 22

Omgevingstemperatuur: $-70^{\circ}\text{C} \leq \text{Ta} \leq 220^{\circ}\text{C}$

Materiaal: messing vernikkeld

Conform de standaards: IEC 60079 en EN60079

Technical data:

Ex mark: Ⓢ I/II 2G Ex db I/IC T6 Gb

Ⓢ I/II 2G Ex eb I/IC T6 Gb


Ⓢ III 2D Ex tb IIIC T80° Db IP66

Can be used in zone 1, 2, 20, 21 and 22

Ambient temperature: $-70^{\circ}\text{C} \leq \text{Ta} \leq 220^{\circ}\text{C}$

Material: brass nickel plated

Meets the standards: IEC60079 and EN60079

Afbeelding Illustration	Grootte Size	Type
	M 16	IEART.M16
	M 20	IEART.M20
	M 25	IEART.M25
	M 32	IEART.M32
	M 40	IEART.M40
	M 50	IEART.M50
	M 63	IEART.M63
	M 75	IEART.M75
	M 90	IEART.M90
	3/8" NPT	IEART.N3/8"
	1/2" NPT	IEART.N1/2"
	3/4" NPT	IEART.N3/4"
	1" NPT	IEART.N1"
	1 1/4" NPT	IEART.N1 1/4"
	1 1/2" NPT	IEART.N1 1/2"
	2" NPT	IEART.N2"
	2 1/2" NPT	IEART.N2 1/2"
	3" NPT	IEART.N3"
	PG 13,5	IEART.P13
	PG 16	IEART.P16
	PG 21	IEART.P21
	PG 29	IEART.P29
	PG 36	IEART.P36