

Glasvezelversterkte polyamide LED armaturen Ex de Glass fiber reinforced polyester LED lighting fixtures Ex de

Technische informatie:

Ex markering: Ⓜ II 2G Ex db eb mb op is q IIC T5/T44 Gb
Ⓜ II 2D Ex tb op is IIIC T80°C Db
Geschikt voor zone 1, 2, 21 en zone 22
Omgevingstemperatuur T5: -25°C tot +40°C
Omgevingstemperatuur T4: -25°C tot +55°C
Beschermingsgraad: IP66
Spanning: 100~250 VAC - 50/60Hz
Voorzien van 1 of 2 stuks LED unit 30 Watt
Kleur 5700 K
Kabelingangen: 3xM25
Aansluitingen: 4 mm²
Materiaal behuizing: glasvezelversterkt polyester
Materiaal kap: polycarbonaat

Uitvoering met batterij tbv noodverlichting.
Laadtijd: 24 uur
Noodverlichting duur: >120 min.


Conform de standaards: EN60079

Technical data:

Ex mark: Ⓜ II 2G Ex db eb mb op is q IIC T5/T4 Gb
Ⓜ II 2D Ex tD IIIC T80°C Db
Can be used in zone 1, 2, 21 and zone 22
Ambient temperature range T5: -25°C to +40°C
Ambient temperature range T4: -25°C to +55°C
Degree of protection: IP66
Voltage: 100~250 VAC - 50/60Hz.
Complete with 1 or 2 pcs LED unit 30Watt
Colour 5700 K
Cable entries: 3xM25
Connections: 4 mm²
Material body: glas fibre reinforced polyester
Material cover: polycarbonate

Version with battery for emergency lighting, only T4:
Charging time: 24 hour
Emergency light duration: > 120 min.

Meets the standards: EN60079

Afbeelding Illustration	Vermogen Power	Lumen	Gewicht Weight	Type
 Paalopzet armatuur Pole mounted fixture	1 x 30W	Excl. diffusor - 3396 Incl. diffusor - 2923	5.5 kg	Z0865 / 1xLED30W□-P
	2 x 30W	Excl. diffusor - 6836 incl. diffusor - 5868	8.9 kg	Z0866 / 2xLED30W□-P
	1 x 30W Emergency -10W	Excl. diffusor - 2920 / 893 incl. diffusor - 2377 / 712	8.6 kg	Z0865 / 1xLED30W□-P-YJ
	2 x 30W Emergency -10W	Excl. diffusor - 5978 / 1794 incl. diffusor - 4671 / 1435	12.1 kg	Z0866 / 2xLED30W□-P-YJ

1 = zonder diffusor / 2 = met diffusor
1 = without diffusor / 2 = with diffusor

Lichtkarakteristiek Luminous intensity curve

